

Rigiton - stropne perforirane ploče

Rigiton ploče su perforirane akustične gips kartonske ploče koje su uz iznimnu estetsku vrijednost izuzetni absorberi zvuka u prostoriji te na taj način pridonose sjajnoj akustici prostora.

Rigiton ploče se isporučuju u više vrsta perforacija, a prema dodatnim performansama dijelimo ih na slijedeći način:

Rigiton Ambiance (AIR)- dodavanjem minerala Zeolita u jezgu ploče postižemo dodatno uklanjanje neugodnih mirisa i smanjenje razine formaldehida u prostoru.

Rigiton Climafit- dodavanjem grafitnih vlakana u jezgu postiže se velika toplinska provodljivost ploča ($\lambda=0,52$ W/mK) te se radi toga koriste kao dio sustava stropnih grijanja i hlađenja uz istovremene akustičke performanse.

Rigiton Climatop- povećana toplinska provodljivost ($\lambda=0,28$ W/mk) također za upotrebu u sustavima stropnog grijanja i hlađenja

Rigiton Primeline- Novi jednostavniji i brži način montaže i obrade spojeva pomoću trakice i posebnih masa za gletanje. Smanjuje vrijeme montaže.

Rigiton Ambiance stropne ploče













Pravilna perforacija

Tip	Dimenzija	Fuga za špahtlanje
RLA 6/18	1188 x 1998 mm	•
RLA 8/18	1188 x 1998 mm	•
RLA 10/23	1196 x 2001 mm	•
RLA 12/25	1200 x 2000 mm	•
RLA 15/30	1200 x 1980 mm	•
RLA 8/15/20	1200 x 2000 mm	•

Kvadratna perforacija

Tip	Dimenzija	Fuga za špahtlanje
QLA 8/18	1188 x 1998 mm	•
QLA 12/25	1200 x 2000 mm	•

Izgled perforacija

Pravilni izmak istih kružnih perforacija					
	6/18	8/18	10/23	12/25	15/30
Neppravilna izmak različitih kružnih perforacija					
	8-15/20	8-15/20 super	12-20/35		
Pravilni izmak različitih kružnih perforacija					
	8-12/50	12-20/66			
Pravilni izmak istih kvadrata perforacija					
	8/18 Q	12/25 Q			