

MERCURY ACRYLIC MASTIC

1. PRODUCT DESCRIPTION

Trade Name: Mercury Acrylic Mastic

Product Description: Mercury Acrylic Mastic is an one part acrylic sealent.

2. TECHNICAL DATA

Specific Gravity: 1,65 ±0,03 gr/cm³

Surface-drying Time: 15-60 min. (23 °C % 50 moisture)

Drying Time: : 2 mm/24 h (23 °C , %50 moisture)

pH: 7.5-9

Weight loss : %18

Colours: White, black, grey, brown, gold oak,

Consistence: Paste

3. APPLICATIONS

Expanding fuga between prefabricate construction element.

Assembly wood, PVC, iron and aliminium joinery.

Joints in stone, wood, concreete, plaster and brick works etc.

Sealing of window and door frame to masonry

4. INSTRUCTIONS

Clean application place (dry and free of grease and dust).

Mask joint edges with adhesive tape.

Cut to open cartridge screw nozzle on cartridge and cut of tip at desired angle.

Insert cartridge in gun.

5. PACKAGING

Cartridges of 500 g.,(30 pcs in box), buckets of 5, 10, 25 and 300 kg.

6. STORAGE AND SHELF LIFE

Months in unopened packing in a cool, dry, storage place at temperatures between +5 °C and +25 °C

7. WARNINGS/ SAFETY PRECAUTIONS

Protect from sunlight and freezing.

Wear any liquid-tight rubber or vinyl gloves.

Consult Material Safety Data Sheet for further information.